



SMA Plastic-Encapsulate Diodes

SS310L

Schottky Rectifier Diodes

Features


- $I_{F(AV)}$ 3A
- V_{RRM} 100V
- High surge current capability
- Polarity: Color band denotes cathode

Applications

- Rectifier

Marking

- SS310L



Limiting Values(Absolute Maximum Rating)

Item	Symbol	Unit	Test Conditions	SS310L
Repetitive Peak Reverse Voltage	V_{RRM}	V		100
Maximum RMS Voltage	V_{RMS}	V		70
Maximum DC Blocking Voltage	V_{DC}	V		100
Average Forward Current	$I_{F(AV)}$	A	60Hz Half-sine wave, Resistance load, FIG.1	3.0
Surge(Non-repetitive)Forward Current	I_{FSM}	A	60Hz Half-sine wave, 1 cycle, $T_a=25^\circ C$	120
Junction Temperature	T_J	°C		-55~+150
Storage Temperature	T_{STG}	°C		-55 ~ +150

Electrical Characteristics ($T = 25^\circ C$ Unless otherwise specified)

Item	Symbol	Unit	Test Condition	SS310L
Peak Forward Voltage	V_F	V	$I_F=3.0A$	0.57(TYP) 0.60(MAX)
Peak Reverse Current	I_{RRM1}	mA	$V_{RM}=V_{RRM}$	0.02
	I_{RRM2}		$T_a=100^\circ C$	20
Thermal Resistance(Typical)	$R_{\theta J-A}$	°C/ W	Between junction and ambient	55
	$R_{\theta J-L}$		Between junction and terminal	17

Notes:

Thermal resistance from junction to ambient and from junction to lead mounted on P.C.B. with 0.2" x 0.2" (5.0 mm x 5.0 mm) copper pad areas

Typical Characteristics

FIG.1: FORWARD CURRENT DERATING CURVE




FIG.2: MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG.3: TYPICAL FORWARD CHARACTERISTICS






FIG.4: TYPICAL REVERSE CHARACTERISTICS




SMA Package Outline Dimensions



Dimensions in inches and (millimeters)

SMA Suggested Pad Layout



Note:

1. Controlling dimension: in millimeters.
2. General tolerance: $\pm 0.05\text{mm}$.
3. The pad layout is for reference purposes only.

Reel Taping Specifications For Surface Mount Devices- SMA




FIG:CONFIGURATION OF SURFACE MOUNTED DEVICES TAPING

ITEM	SYMBOL	SMAG mm(inch)
Carrier width	A	2.79 ± 0.1 (0.110 ± 0.004)
Carrier length	B	5.33 ± 0.1 (0.210 ± 0.004)
Carrier depth	C	2.36 ± 0.1 (0.093 ± 0.004)
Sprocket hole	d	1.55 ± 0.05 (0.061 ± 0.002)
Reel outside diameter	D	279 ± 2.0 (11 ± 0.079)
Reel inner diameter	D1	75 ± 1.0 (2.95 ± 0.039)
Feed hole diameter	D2	13 ± 0.5 (0.512 ± 0.020)
Stroket hole position	E	1.75 ± 0.1 (0.069 ± 0.004)
Punch hole position	F	5.5 ± 0.05 (0.217 ± 0.002)
Punch hole pitch	P	4.0 ± 0.1 (0.157 ± 0.004)
Sprocket hole pitch	P0	4.0 ± 0.1 (0.157 ± 0.004)
Embossment center	P1	2.0 ± 0.1 (0.079 ± 0.004)
Total tape thickness	T	0.28 ± 0.02 (0.011 ± 0.0008)
Tape width	W	12.0 ± 0.2 (0.472 ± 0.008)
Reel width	W1	16.8 ± 2.0 (0.661 ± 0.079)

NOTE:Devices are packed in accordance with EIA standard RS-481-A and specification given above.